

## WOOD H944 XTREM

### HYBRID MULTI-PURPOSE ADHESIVE

#### KEY BENEFITS

- Can be used universally
- Very good adhesion
- For all surfaces
- Ready for use
- Stable, non-slip



#### APPLICATIONS

WOOD H944 XTREM is a moisture-curing 1K hybrid multipurpose adhesive based on SMP technology. WOOD H944 XTREM is very low emission according to GEV- EMICODE EC1, solvent-free and odourless.

#### DESTINATIONS

WOOD H944 XTREM is highly elastic with very high initial adhesion and very good adhesion properties on absorbent and non-absorbent surfaces. Metal substrates must be degreased.

#### Areas of application :

- Building
- Wood materials
- Kitchen worktops
- Sanded epoxy resin coating

#### Associated wood floor coverings :

- For laying parquet and wooden boards
- On walls and floors areas
- On floor and wall surface
- For parquet flooring as well as gypsum and wood substrates
- On special substrates such as metal, aluminum, plaster, gypsum- cardboard and ceramic
- Load-bearing substrates

#### PRODUCT CHARACTERISTICS

<b>Composition/ colour</b>	Silane-modified polymers / orange brown
<b>Open time*</b>	40 min
<b>Walk on time*</b>	12 hours
<b>Curing time* / Floor installation</b>	After 12 hours
<b>Coverage</b>	1,2-1,3 kg/m <sup>2</sup>
<b>Packaging</b>	Plastic bucket 15 kg

\*these times are determined at +23° C and 50 % relative humidity on normally absorbent substrates

## SUBFLOOR PREPARATION

### CLEANING PREPARATION

The substrate must be level, permanently dry, clean, free from cracks, and resistant to tension and pressure. If necessary, metals must be derusted or degreased.

Due to the very good adhesion properties of WOOD H944 XTREM, the multi-purpose adhesive can be applied without primer to properly cleaned substrates.

### METHOD OF USE

Temper the adhesive to at least + 18 °C before use.

After opening, peel off the protective film and remove any surface skin that may have formed, do not un-mix.

Do not use WOOD H944 XTREM at component and ambient temperatures below + 10 °C.

WOOD H944 XTREM is applied to the substrate with a suitable notched trowel. The parquet is laid into the adhesive bed within 40 minutes and pressed firmly into place.

Adhesive stains must be removed immediately with Nibodean Pro cleaning cloths.

Observe the instructions of the parquet manufacturer, in particular the processing conditions and the area of application.

## COVERAGE

From 1.2 to 1.3 kg/m<sup>2</sup>

## STORAGE STABILITY

Can be stored for 12 months in closed original container. Store in a cool and dry place between + 5 °C and + 25 °C.

## CLEANING

Tools and fresh spillages should be cleaned with White spirit and dry products scraping.

Code	UC	PCB	GENCOD
30615777	15 kg	1	4008373130894

## SAFETY

For more details, consult the safety data sheet on <https://bostikdsd.thewerco.com/default.aspx>

*The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the product, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use under the conditions that will exist at the time of the intended use. Bostik does not warrant the product's suitability for any particular application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.*

BOSTIK TECHNICAL ASSISTANCE

Smart Help +XX XX XXX XXX

