

# STIX A340 LVT PROJECT

## LOW EMISSION DISPERSION ADHESIVE MATERIAL FOR LVT DESIGNER COVERINGS

### KEY BENEFITS

- Very easy to spread
- Long laying time
- Solvent free



### APPLICATIONS

#### DESTINATIONS

STIX A340 LVT PROJECT is a low-emission dispersion adhesive.

#### Associated floor coverings :

- LVT design coverings in planks and tiles
- PVC coverings in sheets and tiles

### PRODUCT CHARACTERISTICS

Composition/ colour	Synthetic resin dispersion / Beige white
Waiting time*	10-15 min
Open time*	25-30 minutes
Walk on time*	24 hours
Curing time*	After 24 hours
Coverage	320 g/m <sup>2</sup>
Application temperature	air 18°C to 23°C Not above 75 % relative humidity.

\*these times are determined at + 23° C and 50 % relative humidity on normally absorbent substrates

## SUBFLOOR PREPARATION

### CLEANING PREPARATION

The subfloor must be level, permanently dry, clean, free of cracks, tensile and compressive strength in accordance with the requirements of DIN 18365 "Floor covering work" and must be properly prepared for installation. Use suitable primers and fillers from our product range. Mastic asphalt screeds and other non-absorbent surfaces should always be levelled out to a minimum layer thickness of 2 mm.

### METHOD OF USE

STIX A340 LVT PROJECT is evenly applied to the substrate with a spatula with suitable TKB serration. For the vapour-tight floor coverings, a flash-off period must be added in advance. The flash-off time is determined by the absorbency of the substrate, the room temperature and the relative air humidity. Then lay the floor covering into the adhesive bed and rub/roll it thoroughly (50 kg articulated roller). After 45 minutes, rub/roll the floor covering again. In areas exposed to direct sunlight, such as floor-to-ceiling windows / conservatories, use a shear-resistant adhesive from our range. Observe the instructions of the flooring manufacturer, especially with regard to the air-conditioning of the flooring.

### OCCUPATIONAL SAFETY AND ENVIRONMENTAL PROTECTION

Please refer to the current product safety data sheet for information on occupational safety and environmental protection.

## COVERAGE

320 g/m<sup>2</sup>

## STORAGE STABILITY

Keep container tightly closed. Store in a cool and dry place.

Protect from frost! Shelf life 12 months.

Code	UC	PCB	GENCOD
30615760	14 kg	1	4008373130528



### SAFETY

For more details, consult the safety data sheet on <https://bostikdsds.thewerco.com/default.aspx>

*The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the product, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use under the conditions that will exist at the time of the intended use. Bostik does not warrant the product's suitability for any particular application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the pat*

### BOSTIK TECHNICAL ASSISTANCE

Smart Help +XX XX XXX XXX

